




Cat6A RJ-45 Keystone Inline Coupler (6-Pack)

TC-KC06C6A (v1.0R)

- 6-pack of Cat6A tool-less keystone jacks
- 180° angle termination design
- Cat6A for steady connection to copper Gigabit & 10G switches
- Compatible with Cat5e, Cat6 and Cat6A cabling
- Gold-plated contacts for improved conductivity and corrosion resistance
- Use with blank keystone patch panels TC-KP24S, TC-KP48S, or TC-KP24SA (sold separately)

TRENDnet's Cat6A RJ-45 Keystone Inline Coupler (6-Pack), model TC-KC06C6A, includes six Cat6A keystone couplers for use with TRENDnet's blank keystone patch panels. These metal keystone jack inline couplers are designed for gigabit and 10G copper Ethernet network applications. Each keystone inline coupler is designed for use with Cat6A cabling, eliminating EMI and crosstalk to ensure peak performance and data integrity. These Cat6A keystone inline couplers feature a convenient tool-less design for easy cable installation.




Cat6A for steady connection to copper Gigabit & 10G switches

Gold-plated contacts for improve conductivity and corrosion resistance



6-pack of Cat6A tool-less keystone inline coupler



Use with TC-KP24S or TC-KP24SA shielded blank keystone patch panel and wall plates (sold separately)

FEATURES



Housing Design

Metal housing design protects against EMI/RFI noise for a more stable connection



Cat6A Performance

Each shielded Cat6A keystone coupler provides up to 10Gbps speeds over 100m (328 ft.) of Cat6A Ethernet cabling



Tool-less Design

Tool-less design with convenient wire separation for easy installation



6-Pack

Includes six Cat6A keystone jack inline couplers for use with TRENDnet's blank shielded keystone patch panel and wall plates



Metal Construction

Each inline coupler features an all-metal design for long lasting durability

SPECIFICATIONS

Features

- 6-pack of Cat6A tool-less keystone inline coupler
- Cat6A for steady connection to copper Gigabit & 10G switches
- Gold-plated contacts for improve conductivity and corrosion resistance
- Use with TC-KP24S or TC-KP24SA shielded blank keystone patch panel and wall plates (sold separately)

Dimensions

- 38 x 22 x 17mm (1.5 x 0.87 x 0.67 in.)

Weight

- 15g (0.45 oz.)

Warranty

- 2 year

Package Contents

- TC-KC06C6A x 6

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.