

## **TE-PCI** *High Performance Plug-n-Play Ethernet Adapter*


The TE-PCI is a jumperless, plug and play, 32-bit Ethernet adapter featuring half/full duplex operations. The TE-PCI utilizes the latest PCI Bus Mastering technology to process network packets with minimal CPU utilization..

Taking advantage of Bus Mastering technology, 32-bit bus width and speed up to 33MHz, the TE-PCI/W is superior to all ISA adapters. It is equipped with both BNC and RJ-45 connectors, includes drivers for every popular network operating system and is backed by TRENDware's 5 Year Parts and Labor Warranty.



### **FEATURES**

- > Compliant with IEEE 802.3 10Base-2 and 10Base-T Ethernet standards
- > Full-duplex operation at 10Base-T connection
- > Compliant with PCI Local Bus Specification 2.0
- > Simply insert the card and it will be automatically configured in a PnP system
- > Supports PCI Bus Slave mode
- > Supports Multi-thread Operation
- > Supports Virtual Memory
- > NE2000 Compatible
- > Auto-sensing connector in use
- > On-board socket for optional Boot ROM
- > External LED Indicators for troubleshooting (LINK and TRAFFIC)
- > 10Mbps (Half duplex)/20Mbps (Full duplex) Transfer Rate
- > 5 Year Warranty



# TE-PCI

## High Performance Plug-n-Play Ethernet Adapter

### SPECIFICATIONS

**Standards:**

- IEEE 802.3 10Base-2 and 10Base-T

**On-board Connector:**

- RJ-45 and BNC

**Media Interface:**

- UTP Cat. 3, 4, 5; EIA/TIA-568 non-standard 100-ohm STP cable; RG-58A/U coaxial cable

**Data Bus Supported:**

- 32-bit, PCI Local Bus Specification 2.0 (Bus Master)

**IRQ's Supported:**

- Assigned by the BIOS to a free IRQ (interrupt) number

**I/O Base Address:**

- Assigned by the BIOS to a free I/O address block

**LAN Chipset:**

- DEC 32-bit Intelligent Ethernet interface controller

**Boot ROM Size:**

- 16Kb

**FCC Compliance:**

- FCC Class A certification;  
FCC Class B certification

**CE Mark:**

- Compliance with EMI EN50081-1, EN55022, EMS EN50082-1, IEC 801-2 (ESD), IEC 801-3 (RS), IEC 801-4 (EFT)

**Power Consumption:**

- 2.72W max.

**Temperature:**

- Operating: 32° - 131°F (0° - 55°C)  
• Storage: -4° - 176°F (-20° - 80°C)

**Operating Humidity:**

- 10 to 90%, non-condensing



### PRODUCT INFORMATION

**TE-PCI**

32-bit PCI Plug-n-Play Ethernet Adapter  
with BNC + RJ-45 Connectors

### ORDERING INFORMATION

**TRENDware International, Inc.**

3135 Kashiwa Street  
Torrance, CA. 90505. USA  
Tel: 310-891-1100  
Fax: 310-891-1111  
Web: [www.TRENDNET.com](http://www.TRENDNET.com)  
Email: [sales@trendware.com](mailto:sales@trendware.com)

**To Order Please Call:**  
**1-888-326-6061**