



TE-TT AUI-to-RJ-45 Transceiver

The TE-TT Ethernet transceiver is IEEE 802.3 standard Attachment Unit Interfaces (AUI) that provides quick and easy attachment from a host to any Ethernet media types, including thin coax, 10Base-T unshielded twisted-pair and optic fiber. The transceiver is attached to the host via a DB-15 AUI connector.

Using VLSI transceiver chips for high hardware reliability, the TE-TT transceiver also provides heartbeat, jabber and isolation voltage. To enhance installation compatibility, a SQE jumper is added for selection of the Heartbeat function as well as diagnostic LEDs as standard features.



FEATURES

- Comply with IEEE 802.3 and Ethernet 1.0/2.0 specifications
- Selectable SQE (heartbeat) enable/disable
- Isolation voltage between network cable and transceiver cable
- Directly attach to host's AUI connector without transceiver cable
- 10Mbps transfer rate
- 5 Year Warranty

SPECIFICATIONS

Standards:

- IEEE 802.3 Ethernet standard

Diagnostic LEDs:

- Transmit, receive, collision, jabber

PRODUCT INFORMATION

- **TE-T2:** AUI-to-BNC Transceiver
- **TE-TT:** AUI-to-RJ-45 Transceiver
- **TE-TF:** AUI-to-ST Transceiver
- **TE-TFT:** UTP to ST Transceiver for Fiber Optic Cable
- **TE-TC:** BNC-to-UTP Transceiver

ORDERING INFORMATION

TRENDware International, Inc.
3135 Kashiwa Street
Torrance, CA. 90505. USA
Tel: 310-891-1100
Fax: 310-891-1111
Web: www.TRENDNET.com
Email: sales@trendware.com

**To Order Please Call:
1-888-326-6061**