





3-Port Print Server TE100-P21 (v3.0R)

TE100-P21 is a Fast Ethernet print server that transforms a stand-alone USB or Parallel printer into a shared network printer. The TE100-P21 is compatible with 10Mbps or 100Mbps Ethernet network and it has two USB 2.0 and one Parallel printer port. Network professionals can easily manage the print server using Web Browser and utilize the TE100-P21 to promote productivity in a workgroup environment with low equipment cost.

FEATURES


- Compliant with USB 2.0 high-speed printing and DB25 Parallel printing
- One RJ-45 10/100Mbps Auto-MDIX Fast Ethernet Port
- · Printing over email and email notification
- · LPR printing for windows
- IPP printing for Windows 7/Vista/XP/2000
- Supports Universal Plug and Play (UPnP) for Windows 7/ Vista/ 2003 Server/ XP
- Supports Windows Graphical Device Interface (GDI) Printers*
- Supports second HTTP port for remote web configuration
- Supports Macintosh Rendezvous Zero Configuration**
- Supports SNMP v1.0 and MIBII (RFC 1213)
- Web-based (HTTP) configuration
- · Windows-based setup wizard and configuration utility
- · Built-in Flash Memory for Easy Firmware Upgrade and Configuration File Save & Restore
- 3-years limited warranty
- * GDI feature is only compatible with HP GDI printer
- ** Mac Systems are only compatible with Post-Script printers



SPECIFICATIONS

HARDWARE	
Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX
Printer Interface	 2 x USB 2.0 type A port 1 x Parallel DB-25 (female) port
LAN	10/100Mbps Auto-MDIX RJ-45 port
LED	Power, LAN, USB1, USB2, LPT
Transport Protocol	TCP/IP, SMB, NetBEUI, AppleTalk
TCP/IP Protocol Supported	BOOTP, SNMP, Telnet, TFTP, FTP, LPD, RARP, DHCP, IPP
Supported OS	 Windows 7(32/64-bit)/Vista(32/64-bit)/2003 Server/XP(32/64-bit)/2000/ME/98SE Netware 5.x NDPS LPR Remote Printing (TCP/IP) HP-UX Unix, Sun OS, Solaris, SCO Unix, AIX Unixware, Linux & Mac OS 10.1~10.6
Management	Windows Utility or Web-browser configuration
Power	5V DC 2.5A external power adapter
Dimensions	• 206 x 122 x 34mm (8.1 x 4.8 x 1.3 in.)
Weight	• 289 g (10.2 oz.)
Temperature	 Operating: 0°~50°C (32°~122°F) Storage: -25°~55°C (-13°~131°F)
Humidity	Max. 90% (non-condensing)
Certifications	• CE, FCC

NETWORKING SOLUTIONS



PACKAGE CONTENTS

TE100-P21
Multi-Language Quick Installation Guide
CD-ROM (Utility & User's Guide)
Power Adapter (5V DC, 2.5A)

RELATED PRODUCTS

TE100-P1U	1-Port Print Server
TE100-MFP1	1-Port Multi-Function USB Print Server
TEW-MFP1	1-Port Wireless N Multi-Function USB Print Server

CONTACT INFORMATION

TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com **1-888-326-6061**