



TE100-S5Pplus 5-Port 10/100Mbps Auto-MDIX Fast Ethernet Mini Switch

TRENDnet's TE100-S5Pplus, 5-port, palm-sized 10/100Mbps Fast Ethernet Switch, presents the perfect choice for small workgroups for any desktop space. It allows users to simply plug any port to either a 10Mbps or 100Mbps network to multiply bandwidth, boost response time and satisfy heavy load demands. The RJ-45 network ports automatically negotiate between 10Base-T and 100Base-TX network speeds, half- and full-duplex modes, and MDI-II and MDI-X media types. TE100-S5Pplus is truly a Plug-N-Play device, which provides cost-effective and high-performance solutions.



FEATURES

- Compliant with IEEE 802.3 and IEEE 802.3µ standards
- *** 5-port 10/100Mbps connection speed auto-detection
- *** Half- or Full-Duplex operation for each port
- ---- Auto-MDIX media type detection, easy uplink with any port
- ***Non-blocking wire-speed reception and transmission and non-head-of-line-blocking forwarding
- --- Store-and-forward switching method
- Supports IEEE802.3x full-duplex flow control and back pressure half-duplex flow control
- ***Build-in high efficiency 64KB SRAM for packet buffer and 1K MAC addresses table
- --- Comprehensive LED indicators for port status
- *** Wall-Mountable light-weigh plastic housing
- ⇒ 5-year warranty

BENEFITS

- Easy Installation:
 Designed to link 10Mbps and
 100Mbps with 5 ports for an easy connection.
- respective to the composition of the composition of
- *** Expandability: All ports support 200Mbps (in full-duplex mode), expanding from any port and for any number of Switches.
- **Easy Migration:** Easy upgrade to Fast Ethernet without reconfiguration.
- Dependability: Parallel store-andforward architecture allows direct transfer.

TE100-S5Pplus 5-Port 10/100Mbps Auto-MDIX Fast Ethernet Mini Switch

SPECIFICATIONS

Standards:

 IEEE 802.3 for 10Base-T Ethernet, IEEE 802.3µ for 100Base-TX Fast Ethernet. ANSI/IEEE 802.3 Nway auto-negotiation

Data Transfer Rate:

10/100Mbps (20/200Mbps in full-duplex mode)

Protocol:

CSMA/CD

Connectors:

• 5 UTP/STP RJ-45 Auto-MDIX

Network Media:

- 10Mbps: UTP/STP Cat. 3, 4, 5 EIA/TIA-568, 100 ohm, 100 meters max.
- 100Mbps: UTP/STP Cat. 5 EIA/TIA-568, 100 ohm, 100 meters max.

Data Transfer Rate:

- Ethernet: 10Mbps (half-duplex); 20Mbps (full-duplex)
- Fast Ethernet: 100Mbps (half-duplex); 200Mbps (full-duplex)

Topology:

Star

Diagnostic LEDs:

· Power, Link/Activity

Power:

External power supply, 7.5V, 1A. 2.5 Watts (max.)

Dimensions:

• 125 x 65 x 30 mm (4.9 x 2.55 x 1.1 inches)

Weight:

• 117 g (4 oz.)

Temperature:

- Operating: 0° ~ 40° C (32° ~ 104° F)
- Storage: -10° ~ 70° C (14° ~ 158° F)

Humidity:

- Operating: 10 % ~ 90 % RH
- Storage: 5 % ~ 90 % RH

Certifications:


• FCC, CE, VCCI-B











To Order Please Call: 1-888-326-6061

PRODUCT INFORMATION

*** TE100-S5Pplus: 5-port 10/100Mbps Auto-MDIX Fast Ethernet Mini Switch

8-port 10/100Mbps Auto-MDIX Fast Ethernet Mini Switch

ORDERING INFORMATION

TRENDware International, Inc.

3135 Kashiwa Street Torrance, CA. 90505. USA Tel: 310-891-1100

Fax: 310-891-1111 Web: www.TRENDNET.com Email: sales@trendware.com

