




# SFP Single Mode LC Module (40km)


TEG-MGBS40 (v5.0R)


- Transmission distance of up to 40km (24.85 mi.)
- Duplex LC optical interface
- Supports data rates of up to 1.25Gbps
- Supports 1310nm singlemode network transmissions
- Low Electromagnetic Interference (EMI) design
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Low power consumption

TRENDnet's SFP Single Mode LC Modules are compatible with standard SFP slots found on network switches and fiber converters. Each single mode SFP transceiver is equipped with a duplex LC fiber connection interface, and supports high-speed data rates up to 1.25Gbps. All TRENDnet SFP fiber modules support connections for reliable, long distance network applications.









# **Fiber Applications**

Long-distance fiber networking for manufacturing, business parks, and school campus applications.

## Fiber Mode/Distance

Single mode SFP transceiver spans distances up to 40km (24.85 mi.) at gigabit speeds.

# Compatibility

Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type duplex connectors.

# **FEATURES**



#### **Fiber Distance**

Ideal for long-range networking distances



#### **Fiber Interface**

This single mode fiber SFP transceiver supports LC-type duplex connector



# Fiber Wavelength

Single mode fiber SFP module compatible with 1310nm transmissions



# **Hot-Pluggable SFP**

Hot-pluggable SFP transceiver compatible with an MSA compliant SFP slot

# **SPECIFICATIONS**

#### **Standards**

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

#### **Device Interface**

- SFP MSA Compliant
- · LC duplex connector

## **Data Transfer Rate**

• 1.25Gbps

### Wavelength

• 1310nm

#### **Optical Output Power**

• -3 ~ -2 dBm

#### **Distance**

• 40km (24.8 mi)

#### **Special Features**

- · Hot pluggable
- · Metal enclosure

#### Sensitivity

• -23 dBm

#### **Power**

• Max. Consumption: 0.8W

### **Operating Temperature**

• 0° - 70° C (32° - 158° F)

## **Operating Humidity**

• Max. 95% non-condensing

#### **Dimensions**

• 58 x 13.4 x 12.6mm (2.2 x 0.5 x 0.5 in.)

#### Weight

• 18g (0.6 oz.)

#### Certifications

- CE
- FCC

# Warranty

• 3 year

### **Package Contents**

- TEG-MGBS40
- Quick Installation Guide