



# SFP Single Mode LC Module (80km)

### TEG-MGBS80 (v5.0R)

- Transmission distance of up to 80km (49.7 mi.)
- Duplex LC optical interface
- Supports data rates of up to 1.25Gbps
- Supports 1550nm singlemode network transmissions
- Low Electromagnetic Interference (EMI) design
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Low power consumption

TRENDnet's SFP Single Mode LC Modules are compatible with standard SFP slots found on network switches and fiber converters. Each single mode SFP transceiver is equipped with a duplex LC fiber connection interface, and supports high-speed data rates up to 1.25Gbps. All TRENDnet SFP fiber modules support connections for reliable, long distance network applications.

## TEG-MGBS80

**Fiber Applications** 

Long-distance fiber networking for manufacturing, business parks, and school campus applications.

# **FEATURES**

9	Fiber	Dis	tar	ICe
•				

Ideal for long-range networking distances

C	
	SFP
μ	

### Hot-Pluggable SFP

Hot-pluggable SFP transceiver compatible with an MSA compliant SFP slot

# **SPECIFICATIONS**

### **Standards**

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

### **Device Interface**

- SFP MSA Compliant
- LC duplex connector

### **Data Transfer Rate**

• 1.25Gbps

#### Wavelength

• 1550nm

### **Optical Output Power**

• -2 ~ 3 dBm

#### Distance

• 80km (49.7 mi)

#### Special Features

- Hot pluggable
- · Metal enclosure

#### Sensitivity

-26 dBm

#### Power

• Max. Consumption: 0.8W

### **Operating Temperature**

• 0° - 70° C (32° - 158° F)

#### **Operating Humidity**

Max. 95% non-condensing

#### Dimensions

• 58 x 13.4 x 12.6mm (2.2 x 0.5 x 0.5 in.)

### Weight

• 18g (0.6 oz.)

#### Certifications


- CE
- FCC

#### Warranty

3 year

### Package Contents


- TEG-MGBS80
- Quick Installation Guide



Fiber Mode/Distance

Single mode SFP transceiver spans distances

up to 80km (49.7 mi.) at gigabit speeds.




Compatibility

Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type

duplex connectors.





**Fiber Interface** This single mode fiber SFP transceiver

supports LC-type duplex connector



**Fiber Wavelength** Single mode fiber SFP module compatible with 1550nm transmissions