## TRENDNET



## 4-Pack SFP Multi-Mode LC Module (550m)


#### TEG-MGBSX/4 (v3.3R)


- Includes four TEG-MGBSX SFP modules
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Supports data rates of up to 1.25Gbps
- Transmission distance of up to 550m (1804 ft.)
- · Low Electromagnetic Interference (EMI) design
- Supports 850nm multi-mode network transmissions
- Duplex LC optical interface
- Low power consumption


TRENDnet's 4-Pack SFP Multi-Mode LC Module, model TEG-MGBSX/4, includes four fiber gigabit SFP modules that are compatible with standard SFP slots found on network switches and fiber media converters. Each Multi-Mode SFP module is equipped with a duplex LC fiber connection interface, and supports gigabit multi-mode fiber connections for long distance networking applications.











**Fiber Applications** Long distance fiber networking for manufacturing, business parks, and school campus applications. **Fiber Mode/Distance** Multi-Mode transceiver spans distances up to 550m (1804 ft.) at gigabit speeds.

#### **Compatibility** Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type duplex connectors.

### **NETWORKING SOLUTION**



# TRENDNET®

Hot-Pluggable SFP Hot-pluggable SFP transceiver compatible with an MSA compliant SFP slot



Fiber Interface LC-type duplex connector

### **SPECIFICATIONS**

#### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

#### **Device Interface**

- SFP MSA Compliant
- LC duplex connector

#### **Data Transfer Rate**

• 1.25Gbps

#### Wavelength

• 850nm

#### **Optical Output Power**

• -9 ~ -3 dBm

#### Distance

• 550m (1804 ft.)

#### **Special Features**

- Hot pluggable
- Metal enclosure

#### Sensitivity

• -20 dBm

#### Power

• Max. Consumption: 0.8W

#### **Operating Temperature**

• 0° - 70° C (32° - 158 °F)

#### Operating Humidity

Max. 85% non-condensing

#### Dimensions

• 57 x 13 x 12 mm (2.2 x 0.5 x 0.5 in.) per unit

#### Weight

• 18g (0.6 oz.) per unit

#### Certifications

- CE
- FCC

#### Warranty

3 year

#### **Package Contents**

- 4 x TEG-MGBSX
- Quick Installation Guide

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • sales@trendnet.com • www.TRENDnet.com

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.





Fiber Wavelength Compatible with multi-mode 850nm transmissions



Fiber Distance Supports networking for distances up to 550m (1804 ft.)