




# SFP Multi-Mode LC Module (550m)


## TEG-MGBSX (4.0R)


- Transmission distance of up to 550m (1804 ft.)
- Supports data rates of up to 1.25Gbps
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Low Electromagnetic Interference (EMI) design
- Supports 850nm multi-mode network transmissions
- Duplex LC optical interface
- Low power consumption

TRENDnet's SFP Multi-Mode LC Module, model TEG-MGBSX, are compatible with standard SFP slots found on network switches and fiber media converters. The Multi-Mode SFP LC module is equipped with a duplex LC fiber connection interface, and supports gigabit multi-mode fiber connections for long distance networking applications.









Fiber Applications Long distance fiber networking for manufacturing, business parks, and school campus applications.

## Fiber Mode/Distance

Multi-Mode transceiver spans distances up to 550m (1804 ft.) at gigabit speeds.

## Compatibility

Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type duplex connectors.

# **NETWORKING SOLUTION**



# TRENDNET

# **FEATURES**

(		
	CED	
	366	
L		

Hot-Pluggable SFP Hot-pluggable SFP LC transceiver compatible with an MSA compliant SFP slot

Fiber Interface SFP duplex LC connector

# **SPECIFICATIONS**

#### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

#### **Device Interface**

- SFP MSA Compliant
- LC duplex connector

#### Data Transfer Rate

• 1.25Gbps

#### Wavelength

• 850nm

#### **Optical Output Power**

• -9 ~ -3 dBm



## **Fiber Wavelength**

Compatible with multi-mode 850nm transmissions



#### Fiber Distance

The multi-mode SFP supports networking for distances up to 550m (1804 ft.)

#### Distance

• 550m (1804 ft.)

#### **Special Features**

- Hot pluggable
- Metal enclosure

#### Sensitivity

• -20 dBm

#### Power

Max. Consumption: 0.8W

#### **Operating Temperature**

• 0° - 70° C (32° - 158 °F)

## **Operating Humidity**

Max. 85% non-condensing

#### Dimensions

• 57 x 13 x 12 mm (2.2 x 0.5 x 0.5 in.)

#### Weight

• 18g (0.6 oz.)

#### Certifications

- CE
- FCC

#### Warranty

• 3 year

#### Package Contents

- TEG-MGBSX
- Quick Installation Guide

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.