



24-port Gigabit Switch

TEG-S240TX [E1.0R]

TEG-S240TX is a high performance 24-port rack mountable Copper Gigabit Switch. With auto-negotiation technology, the TEG-S240TX automatically negotiates between 10Base-T, 100Base-TX and 1000Base-T network speeds, as well as half and full duplex modes. The Auto-MDIX feature on each port automatically detects and adjusts connection type with either straight-through or crossover cable. Providing simple migration, scalability, and flexibility to handle new applications and data types, TEG-S240TX is a highly reliable and cost effective solution for high-speed network applications.

FEATURES

- 24 x 10/100/1000Mbps Auto-Negotiation and Auto-MDIX ports
- Full/Half Duplex Transfer Mode for Each Port (1000Base-T connections support full-duplex mode only)
- Store and Forward Switching Method
- High Performance Single-Chip Design
- Non-Blocking Wire Speed Reception and Transmission
- IEEE 802.3x Full-Duplex Flow Control
- Integrated Address Look-Up Engine, Supports 8k Absolute MAC Address
- 500KBytes RAM Data Buffering
- Extensive Front Panel Diagnostic LEDs
- Standard 19" Rack-Mount Size
- 3-Year Limited Warranty


24-port Gigabit Switch

TEG-S240TX (E1.0R)

SPECIFICATIONS

Hardware	
Standard	• IEEE 802.3 10Base-T • IEEE 802.3u 100Base-TX • IEEE 802.3ab 1000Base-T • IEEE 802.3x Full Duplex Flow Control
Network Media	• Ethernet: 2-pair UTP Cat. 3, 4, 5, up to 10Mbps • Fast Ethernet: 2-pair UTP Cat. 5, up to 100Mbps • Gigabit: 4-pair UTP Cat. 5, 5E, 6, up to 1000Mbps
Transmission Method	• Store-and-Forward
Data Transfer Rate	• Ethernet: 10Mbps/20Mbps (Half/Full Duplex) • 100Mbps: 100/200Mbps (Half/Full-Duplex) • Gigabit: 2000Mbps (Full-Duplex)
Switch Fabric	• 48Gbps forwarding capacity
Data RAM Buffers	• 500Kbytes
Filtering Address Table	• 8K entries per device
LED	• Per Unit: Power • Per Port: Link/ACT, 1000M, 100M
Power	• 100 ~ 240VAC 50/60Hz, internal Power Supply
Power Consumption	• 19 watts (max)
Dimension	• 440 x 140 x 44mm (17.3 x 5.5 x 1.73in.)
Weight	• 3kg (6.6lb)
Temperature	• Operating: 0°C ~ 40°C (32°F ~ 104°F) • Storage: -10°C to 70°C (14°F to 158°F)
Humidity	• 10 % ~ 90 % (non-condensing)
Certifications	• FCC, CE

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEG-S240TX
- Multi-Language Quick Installation Guide
- Rackmount Kit
- Power Cord

RELATED PRODUCTS

TEG-S160TX	16-Port Gigabit Switch
TEG-PCITXR	Gigabit PCI Adapter
TEG-PCBUSR	Gigabit PC Card

ORDERING INFORMATION

TRENDNET[®]

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

