



## 8-Port Gigabit GREENnet Switch


#### TEG-S80g (v4.1R)

- Plug and play installation
- 8 x Gigabit ports
- 16Gbps switching capacity
- Up to 70% energy savings with GREENnet technology\*
- Wall mountable metal housing

The 8-Port Gigabit GREENnet Switch, model TEG-S80g, provides high bandwidth performance, ease of use, and reliability, all while reducing power consumption by up to 70%\*. GREENnet technology automatically adjusts power consumption as needed, resulting in substantial energy savings. Embedded GREENnet technology works right out of the box with no management requirement.

Boost office network efficiency and eliminate network congestion with gigabit speeds and a total switching capacity of 16Gbps with full-duplex mode. Integrate this sturdy metal switch for reliable high speed network connectivity.





**Gigabit Speeds** 

8 gigabit ports provide high-speed network

connections to devices and a 16Gbps

switching capacity allows data traffic to flow

smoothly, reducing traffic bottlenecks.

## ▲ 15cm →

**Compact Design** 


With a compact and lightweight metal housing

design, this switch is well-suited for desktop

installations. Its fanless design is perfect for

quiet environments that require silent

operation.



#### **Energy Savings**

Embedded GREENnet technology provides cost savings and reduces power consumption by up to 70%, by limiting port power consumption during periods of low link utilization.

# 

## **NETWORKING SOLUTION**

### R TRENDNET

## FEATURES

#### 2) (3)

Easy Setup Simply power up the switch and plug in connected devices



#### Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 9KB), for increased performance



#### LED Indicators

LEDs convey power, link, and activity

## SPECIFICATIONS

#### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3az

#### **Device Interface**

- 8 x Gigabit ports
- LED indicators

#### **Data Transfer Rate**

- Ethernet: 10Mbps (half duplex), 20Mbps (full duplex)
- Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex)
- Gigabit: 2000Mbps (full duplex)

#### Performance

- Data RAM buffer: 192KB
- Switch fabric: 16Gbps
- MAC address table: 4K
- Forwarding rate: 11.9Mpps (64-byte packet size)
- Jumbo frame: 9KB

#### Special Features

- GREENnet energy saving technology
- · Metal enclosure
- Wall Mountable

#### Power

- Input: 100 240V AC, 50/60Hz, 0.15A
- · Output: 5V DC, 1A external power adapter
- Max. consumption: 4W

#### Fan/Acoustics

· Fanless design

#### MTBF

• 2,082,116 Hours

#### **Operating Temperature**

• 0° – 40° C (32° – 104° F)

#### **Operating Humidity**

Max. 90% non-condensing

#### Dimensions

• 150 x 97 x 28mm (5.9 x 3.8 x 1.1 in.)

#### Weight

365g (12.9 oz.)

#### Certifications

- CF
- FCC

#### Warranty

3 years

#### Package Contents

- TEG-S80g
- Quick Installation Guide
- Power adapter (5V DC, 1A)

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.



#### Ports

**Fanless** 

noise

8 x Gigabit Ethernet ports

Fanless design lowers energy

consumption and eliminates operating

Housing Design Compact and lightweight metal housing

Switching Capacity

16Gbps switching capacity