





300Mbps Wireless N Gigabit Router TEW-639GR(V2.0R)

The 300Mbps Wireless N Gigabit Router offers unsurpassed wireless speed, coverage and reliability. Enjoy up to 14x the speed and 6x the coverage of a wireless g connection*.

Gigabit Wide Area Network and Local Area Network ports transfer your data fast. Wi-Fi certification ensures optimal wireless throughput signal strength and compatibility.

Advanced Multiple Input Multiple Output (MIMO) antenna technology eliminates wireless dead spots. Wireless encryption and a manual on/off wireless switch keep your data safe. Wireless Protected Setup (WPS) integrates other WPS supported wireless adapters at the touch of a button. Seamlessly stream HD media, download files, surf and play games at wireless n Gigabit speed.

- FEATURES •4 x 10/100/1000Mbps Auto-MDIX LAN ports
 - 1 x 10/100/1000Mbps WAN port (Internet)
 - Gigabit LAN ports for high speed network connectivity
 - Compatible with most popular cable/DSL Internet service providers using Dynamic/Static IP, PPPoE, PPTP and L2TP
 - High-speed wireless data rates up to 300Mbps using an IEEE 802.11n connection
 - 3 external antennas provide high-speed performance and expansive wireless coverage
 - Advanced Firewall protection with Network Address Translation (NAT) and Stateful Packet Inspection (SPI)
 - · Access restriction with Internet Access Control; time scheduling and MAC filtering
 - Built-in pre-configured virtual servers and Application Level Gateway services for special Internet applications
 - Universal Plug and Play (UPnP) for auto discovery and support for device configuration of Internet applications
 - Enable/disable wireless functionality with the WLAN on/off toggle switch
 - Multiple pass-through sessions for popular VPN applications (IPSec and PPTP)
 - · Easy setup via Web browser using the latest versions of Internet Explorer, FireFox, Safari and Chrome
 - · One-touch wireless security setup using the Wi-Fi Protected Setup (WPS) button when connecting to a WPS supporting device
 - Complete wireless security with WPA/WPA2, WPA-PSK/WPA2-PSK, and WEP
 - Windows 95/98/NT/2000/XP/2003 Server/Vista/7, Linux and Mac OS supported
 - 3- year limited warranty

300Mbps Wireless N Gigabit Router TEW-639GR(V2.OR)

SPECIFICATIONS

Hardware	
Standards	Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX) and IEEE 802.3ab (1000BaseT)
	Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
WAN	1 x 10/100/1000Mbps Auto-MDIX port (Internet)
LAN	4 x 10/100/1000Mbps Auto-MDIX port
Wireless On/Off Switch	Turn on/off wireless LAN
On/Off Power Switch	Electrical power on/off switch
WPS Button	Wi-Fi Protected Setup (WPS) automated wireless connection push button
Reset Button	Reset button to Factory Default
Connection Type	Dynamic IP, Static (fixed) IP, PPPoE, PPTP, L2TP
NAT Firewall	3K configurable NAT entries; restricted NAPT • IP ranges, port ranges and schedule
	Port triggering for 24 special applications
	ALG support (enable/disable support) –RTP/RTSP, AOL, FTP, ICMP, WMP/MMS, NetMeeting, SIP
WDS	Enable/disable Wireless Distribution System support
UPnP	UPnP IGD 1.0 compliant
DMZ	DMZ host, 24 configurable Virtual Servers and Game Servers
DNS	Static or WAN assigned DNS servers; 4 verified services for DDNS
Internet Access Control	 Time based Internet access; port range/service filtering; Internet domain restriction; 32 user defined schedules, 24 MAC addres filter entries
LED Indicator	• Power, LAN1~LAN4, WAN, WLAN, WPS
Power Switch	On/Off power switch
Power Adapter	12V DC, 1A external power adapter
Power Consumption	• 779mA
Dimension (L x W x H)	• 150 x 163 x 26 mm (5.9 x 6.4 x 1.0 in)
Weight	• 350g (0.8 lb)
Temperature	• Operation: 0°C~ 40°C (32°F~ 104°F); Storage: -20°C~ 60°C (-4°F~140° F)
Humidity	Max. 90% (non-condensing)
Certifications	• CE, FCC
Wireless	
Frequency	• 2.412 ~ 2.472 GHz
Antenna	3 x 4dBi fixed dipole antenna
Modulation	DBPSK/DQPSK/CCK/OFDM (BPSK/QPSK/16-QAM/64-QAM)
Data Rate	802.11b: up to 11Mbps
Security	WEP(HEX/ASCII): 64/128-bit WPA(AES/TKIP): WPA/WPA2-Radius, WPA-PSK/WPA2-PSK
Access Control	MAC Address Filter (Up to 24 entries)
Output Power	802.11b: 18dBm (typical)
Receiving Sensitivity	802.11b: -84dBm (typical) @ 11Mbps 802.11g: -72dBm (typical) @ 54Mbps 802.11n: -65dBm (typical) @300Mbps
Channels	• 1~ 11 (FCC), 1~13 (ETSI)

300Mbps Wireless N Gigabit Router TEW-639GR(V2.OR)

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-639GR
- Multi-Language Quick Installation Guide
- CD-ROM (User's Guide)
- Cat. 5 Ethernet cable (1.5m / 4.9ft)
- Power adapter (12V DC, 1A)

RELATED PRODUCTS

TEW-624UB	300Mbps Wireless N USB 2.0 Adapter
TEW-642EC	300Mbps Wireless N Express card

ORDERING INFORMATION

TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

