



54Mbps 802.11g Wireless Multi-Port Print Server TEW-P21G (B1.0R)

TEW-P21G is a wireless print server that transforms virtually a stand-alone networkable USB or Parallel printer into a shared network printer. The TEW-P21G is compatible with IEEE 802.11g 54Mbps network and it has two USB 2.0 and one Parallel printer port. Network professionals can easily manage the print server using Web Browser and utilize the TEW-P21 to promote productivity in a workgroup environment with low equipment cost.

FEATURES

- Wi-Fi Compliant with IEEE 802.11b/g Wireless Devices
- Built-in 1 Parallel (DB 25) and 2 USB 2.0 (Type A) Printer Port
- One RJ-45 10/100Mbps Auto-MDIX Fast Ethernet Port
- Supports Email Printing and FTP Printing
- Includes LPR Program for Windows 95/98/ME TCP/IP Printing
- Supports IPP Printing for Windows 2000/XP
- Supports second HTTP port for Remote Web Configuration and IPP Printing
- Supports UPnP (Universal Plug and Play) for Windows XP/2003/Vista
- Supports Windows Graphical Device Interface (GDI) Printers*
- Supports Mac 10.2 "Rendezvous" Zero-Configuration Function**
- Latest MIB-II (RFC 1213) for SNMP Standard Management
- IP Assignment Support for DHCP, BOOTP and RARP
- Includes Windows-Based Administrative Program and Web-Based Configuration
- Built-in Flash Memory for Easy Firmware Upgrade and Configuration File Save & Restore
- Printing Access Control/Display and Email Notification for Printer Error Messages
- 3-Years Limited Warranty

* GDI feature is only compatible with HP GDI printer

** Mac Systems are only compatible with Post-Script printers


54Mbps 802.11g Wireless Multi-Port Print Server

TEW-P21G(B1.0R)

SPECIFICATIONS

Hardware	
Standards	• Wired: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX • Wireless IEEE 802.11b/g
Printer Interface	• 1 x Parallel DB25 (Female) Port; 2 x USB 2.0, 1.1 Compliant USB Type A Port
LAN Port	• 10/100Mbps Auto-Negotiation UTP/STP RJ-45 Port
CPU/ SDRAM / Flash ROM	• RDC R2880 100MHz / 8MByte / 2MByte
LED	• Power, Link/Act, WLAN, USB1, USB2, LPT
Transport Protocol	• TCP/IP, SMB, NetBEUI, AppleTalk
TCP/IP Protocol Supported	• BOOTP, SNMP, Telnet, TFTP, FTP, LPD, RARP, DHCP, IPP
OS Support	• Windows 95/98(SE)/ME/NT/2000/XP/2003/Vista • Netware 5.x NDPS LPR Remote Printing (TCP/IP) • HP-UX Unix, Sun OS, Solaris, SCO Unix, AIX • Unixware, Linux & Mac OS (AppleTalk)
Management	• PS Utility or Web-Browser Configuration
Power	• 5V DC 2.5A External Power Adapter
Dimensions	• 195 x 120 x 30mm (7.7 x 4.7 x 1.25 inches) Not including antenna.
Weight	• 300 g (0.75lb)
Temperature	• Operating: 0° C ~50° C (32° F~122° F) • Storage: -25° C ~55° C (-13° F~131° F)
Humidity	• 10%~90% (non-condensing)
Certification	• CE, FCC
Wireless	
Frequency	• 2.4 ~ 2.4835 GHz (Industrial Scientific Medical Band)
Module Technique	• 802.11b: CCK (11 and 5Mbps), DQPSK (2Mbps), DBPSK (1Mbps) • 802.11g: OFDM
Encryption	• 64/128-Bit WEP, WPA-PSK, WPA2 -PSK (TKIP AES)
Antenna	• 2dBi Detached Reverse-SMA (Male) Diversity Antenna
Data Rate	• IEEE 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps • IEEE 802.11b: 11Mbps, 5.5Mbps, 2Mbps and 1Mbps (Auto Fallback)
Channel	• 1~11 Channels (FCC), 1~13 Channels (ETSI)

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-P21G
- Multi-Language Quick Installation Guide
- CD-ROM (Utility & User's Guide)
- Power Adapter (5V DC, 2.5A)

RELATED PRODUCTS

TEW-P1UG	54Mbps 802.11g Wireless USB 2.0 Print Server
TEW-P1PG	54Mbps 802.11g Wireless Parallel Print Server
TE100-P1U	10/100Mbps USB 2.0 Print Server

ORDERING INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

