

## TK-401R / TK-801R / TK-1601R General Quick Reference Sheet

Command	Hot Keys	Front Panel Button	Description
Select Computer	TK-401R / TK-801R Scroll Lock + Scroll Lock + (Y) (Y) = 1-digit port number (1-4) (TK-401R) (Y) = 1-digit port number (1-8) (TK-801R) TK-1601R Scroll Lock + Scroll Lock + (Y) + (Z) (YZ) = 2-digit port number (01-16)	Press any push button	Select the desired computer
Next Higher Computer Channel	Scroll Lock + Scroll Lock + ↑	Press push button for a specific port on the switch	Select the next higher available computer
Next Lower Computer Channel	Scroll Lock + Scroll Lock + ↓	Press push button for a specific port on the switch	Select the next lower computer
Autoscan	Scroll Lock + Scroll Lock + S	—	Autoscan through every connected channel for quick screen browsing of each channel
Autoscan with Programmable Delay Time	Scroll Lock + Scroll Lock + S + (X) (X) = 5 ~ 99 seconds	—	Autoscan through every connected channel for quick screen browsing of each channel in intervals of X seconds
Stop Autoscan	Press any key on keyboard	Press any button or key	Terminate Autoscan activity
Autoscan Beep Sound On/Off	Scroll Lock + Scroll Lock + B	—	Toggle On/Off beep sound during Autoscan mode
Reset KVM	Scroll Lock + Scroll Lock + END	—	

### Note:

The hot key sequence Scroll Lock + Scroll Lock + (Key) denotes that you should hit the individual key consecutively one at a time, not simultaneously.