



## 16-Port 10/100 Mbps 220 Watt AV PoE+ Switch

TPE-1016L (v1.0R)

- 16 x PoE+ Ethernet ports
- 220 Watt power budget
- 3.2 Gbps switching capacity
- Rack mount brackets included
- Fanless design reduces energy consumption and operating noise
- Rear panel ports for easy network integration with your AV rack
- Convenient front-panel 4-digit seven-segment LED display
- Limited Lifetime Warranty\*

TRENDnet's 16 Port Ethernet 220 Watt AV PoE+ Switch, model TPE-1016L, offers 16 x PoE+ Ethernet ports with a total Power budget of 220 Watts. View total power, available power, and power-per-port with a convenient front-panel 4-digit seven-segment LED display. Rear panel Ethernet ports and front panel LEDs easily integrate with your existing Audio & Video (AV) rack solution.



### Hardware Design

Rear panel Ethernet ports and front panel LEDs easily integrate with your existing Audio & Video (AV) rack solution



### 7-Segment LED Display

View total power, available power, and power-per-port



### Power Budget

Up to 220 Watts




### Rack Mountable

Standard 19" 1U design (brackets included)




### Fanless

Fanless design reduces energy consumption and operating noise.




### PoE Camera Flexibility

The switch recognizes non-PoE, PoE (15.4 Watts), and PoE+ (30 Watts) cameras (or other PoE devices) and supplies the required amount of power automatically.




### PoE Power

A 220 Watt PoE power budget supplies up to Sixteen Power over Ethernet devices with PoE power.



### Ethernet Networking

Sixteen 10/100 Mbps Ethernet ports produce a 3.2 Gbps switching capacity to support edge network installations.



- 1 Seven segment display
- 2 Selection button
- 3 LED indicators
- 4 Power port
- 5 On / off Switch
- 6 PoE+ Ethernet ports

## AV Switches: Sample Applications



### Application 1: Restaurants and Bars

In most business environment's, TRENDnet's AV switches will serve a dual purpose. The switches allow business owners to simultaneously manage AV equipment, IP surveillance cameras, and wireless access points.

### Application 2: Homes with Multi-Room AV

TRENDnet AV Series Switches easily expands a home's existing wired network for high bandwidth devices, especially those devices dedicated to multimedia sharing and home security.



### Application 3: NVR and AV Switches Solution

With both sets of ports on the back, TRENDnet AV Series Switches are ideal for use with TRENDnet NVRs. The AV switches are equipped to provide all the power needed to run several TRENDnet surveillance cameras simultaneously.

## Specifications

### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3af
- IEEE 802.3at

### Device Interface

- 16 x 10/100 Mbps Ethernet ports
- LED indicators
- 4-Digit Seven-Segment LED Display

### Data Transfer Rate

- Ethernet: 10 Mbps (half-duplex), 20 Mbps (full-duplex)
- Fast Ethernet: 100 Mbps (half-duplex), 200 Mbps (full-duplex)

### Performance

- Broadcast storm control
- Data RAM Buffer: 400 KB
- Switch Fabric: 3.2 Gbps
- MAC Address Table: 4 K entries
- Forwarding rate: 2.3 Mpps (64-byte packet size)

### Power

- Input: 110 – 240 V AC, 50/60 Hz
- Consumption: 7 Watts (Max. without PD)

### PoE

- PoE overall budget: 220 Watts
- PoE budget per port: 30 Watts
- Pin 1,2 for power+ and pin 3,6 for power- (mode A)
- Over current protection
- Short circuit protection

### Operating Temperature

- 0 – 40 °C (32 – 104 °F)

### Operating Humidity

- Max. 90% non-condensing

### Dimensions

- 440 x 280 x 44 mm (17.3 x 11 x 1.7 in.)

### Weight

- 3.5 kg (7.7 lbs.)

### Certifications

- CE
- FCC
- UL

### Warranty

- Limited Lifetime Warranty\*

### Package Contents

- TPE-1016L
- Quick Installation Guide
- Rack mount kit
- Power cord

TRENDnet offers a limited lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.

