TRENDNET®




6-Port Fast Ethernet PoE+ Switch

TPE-S50 (v2.0R)

- · Easy installation
- 4 x Fast Ethernet PoE+ ports and 2 x Fast Ethernet ports
- 1.2Gbps switching capacity
- 60W PoE budget
- · Wall mountable design
- · Sturdy metal switch
- · Use with TRENDnet's PoE splitter to network and power non-PoE devices
- · Limited Lifetime Warranty


The 6-Port Fast Ethernet PoE+ Switch, model TPE-S50, delivers data and power over existing Ethernet cables to Power over Ethernet (PoE) devices such as access points, VoIP phones, and IP Cameras. It supports both PoE (802.3af) and PoE+ (802.3at) devices with a 60W PoE budget. Plug and play this sturdy metal switch for reliable high speed PoE networking. Its fanless design is perfect for quiet environments that require silent operation.





A 60W PoE power budget supplies up to

four Power over Ethernet devices.



Fast Ethernet


Six Fast Ethernet ports provide a 1.2Gbps switching capacity to support edge network installations.

Compact Design

With a compact and lightweight housing design, this switch is well-suited for desktop installations. Its fanless design is perfect for quiet environments that require silent operation.

Networking Solution

PoE+ Power





PoE+

Supplies up to 30W of PoE+ power per PoE port with a 60W power budget



Ports Four Fast Ethernet PoE+ ports and two Fast Ethernet ports



Switching Capacity 1.2Gbps switching capacity

Wall mountable metal housing

Housing



LED Indicators LED indicators convey port status



TRENDNET®

Specifications

Standards	 IEEE 802.3 IEEE 802.3u IEEE 802.3x IEEE 802.3af IEEE 802.3at IEEE 802.3az
Device Interface	• 4 x 10/100Mbps PoE+ Ports • 2 x 10/100Mbps Ports • LED indicators
Data Transfer Rate	 Ethernet: 10Mbps (half duplex), 20Mbps (full duplex) Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex)
Performance	 Data Ram Buffer: 96KB Switch Fabric: 1.2Gbps MAC Address Table: 2K entries Forwarding rate: 0.89Mpps (64-byte packet size)
Special Features	GREENnet energy saving technology
Power	 Input: 100~240 VAC, 50/60 Hz 1.1A Internal universal switching power Consumption: 65 Watts (max.)
РоЕ	PoE budget: 60 Watts Mode A: Pins 1,2 for power(+) and pins 3,6 for power(-)
Operating Temperature	• 0 – 40 °C (32 - 104 °F)
Operating Humidity	Max. 90% non-condensing
Dimensions	• 168 x 95 x 32 mm (6.6 x 3.7 x 1.6 in.)
Weight	• 504g (17.8 oz.)
Certifications	• CE • FCC
Warranty	Lifetime Warranty*

PACKAGE CONTENTS

- TPE-S50
- Quick Installation Guide
- Power cord (1.2m / 4 ft.)

TRENDnet offers a limited lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • sales@trendnet.com • www.TRENDnet.com

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.