





200Mbps Powerline AV Adapter Kit with Bonus OutletTPL-307E2K (V1.0R)

TRENDnet's 200Mbps Powerline AV Adapter Kit with Bonus Outlet, model TPL-307E2K, comes with everything you need to build an HD Powerline network from any electrical outlet. Connect the first adapter to your network and plug the second adapter into any outlet on your electrical system for instant high speed network access.

Never lose an electrical outlet with the built in outlet on the front of the adapters. The compact housing does not block adjacent electrical outlets. A noise filter maintains optimum connection speeds when household devices create electrical background noise.

The adapters will automatically connect with no installation required—TRENDnet recommends pressing the 'Sync' button to automatically change default encryption keys. Use up to 6 adapters to network devices in different rooms without running new cabling. Power Save mode reduces power consumption by up to 80%. Quality of Service technology prioritizes video, audio, and online gaming. Advanced AES encryption secures your network. This adapter is ideal for use in buildings that interfere with wireless networking signals.

FEATURES

- Includes two TPL-307E adapters
- Compliant with IEEE1901 and HomePlug AV standards
- High speed building-wide networking over an existing electrical system
- 1 x 10/100Mbps Auto-MDIX Fast Ethernet port
- 1 x electrical power socket
- 1 x One-touch Sync button to change the default encryption key
- Three LED indicators: Power (on/off), Powerline Connection (green (best), amber (better), red (good), off(no connection)), Ethernet Connection (solid (connection), blinking (transfer activity), off (no connection))
- · Advanced electrical noise filter boosts performance
- · Share data intensive files, play games, download music, and more at fast data transfer rates
- Advanced 128-bit AES encryption to ensure total network security
- Power Saving mode reduces electrical consumption by 80%
- Neighbor network support for up to 4 overlapping networks
- Network signal transmits up to 300 meters (984ft.)
- Compatible with all operating systems
- Optional management utility compatible with Windows 7 (32/64-bit), Vista (32/64-bit), and XP (32/64-bit) operating systems
- · 3-vear limited warranty
- * Maximum of 6 adapters (nodes) for streaming video across your network.
- ** 200Mbps is the maximum theoretical Powerline data rate. Actual throughput will vary depending on environment.
- *** Networked Powerline devices need to be plugged into power outlets that are on the same electrical system.
- **** GFCI outlets and AFCI circuit breakers may degrade Powerline network signals.

200Mbps Powerline AV Adapter Kit with Bonus Outlet TPL-307E2K (V1.0R)




SPECIFICATIONS

HARDWARE	- La companya di mangantangan pangangan pangangan pangangan pangangan pangangan pangangan pangangan pangangan pan
	IEEE 4004 Have Place AV IEEE 000 2 IEEE 000 2. IEEE 000 2
Standards	• IEEE 1901, HomePlug® AV, IEEE 802.3, IEEE 802.3x, IEEE 802.3u
Interface	 1 x 10/100Mbps Auto-MDIX RJ-45 Port 1 x electrical power socket with noise filtering (12A max. load) Power prong: A: North America Type B (NEMA 5–15) EU: Euro Type C (CEE 7/16) FR: French Type E (CEE 7/5) UK: United Kingdom Type G (BS 1363)
Frequency Band	• 2 ~ 28 MHz
Modulation	OFDM Symbol modulation on link synchronization, 1024/256/64/8 - QAM, QPSK, BPSK, ROBO carrier
Protocols	TDMA and CSMA/CA
Speed	 Powerline: up to 200Mbps** Ethernet: up to 200Mbps with Full Duplex mode
Utility OS Compatibility	• Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit)
Nodes	• Up to 6 (max.)
Overlapping Powerline Networks Supported	Up to 4 (per electrical system)
Coverage	• Up to 300 m (984 ft.)
Security	128-Bit AES (Advanced Encryption Standard)
LED	 Power (PWR) Powerline (PL) Connection Best (Green) Better (Amber) Good (Red) No connection (Off) Ethernet (ETH) Connection Solid Blinking Off
Buttons	Sync, Reset
Dimension (L x W X H)	 A: 122 x 55 x 60 mm (4.8 x 2.2 x 2.4 in.) per unit EU/FR: 122 x 55 x 78 mm (4.8 x 2.2 x 3.1 in.) per unit UK: 122 x 55 x 72 mm (4.8 x 2.2 x 2.8 in.) per unit
Weight	 A: Total Weight: 294 g (10.4 oz) / Per Unit Weight: 147 g (5.2 oz) EU: Total Weight: 336 g (11.8 oz) / Per Unit Weight: 168 g (5.9 oz) FR: Total Weight: 338 g (12 oz) / Per Unit Weight: 169 g (6.0 oz) UK: Total Weight: 350 g (12.4 oz) / Per Unit Weight: 175 g (6.2 oz)
Power Source	• 100~240V AC, 50~60Hz
Consumption	Active mode: 3 Watts (max.)Standby mode: 0.6 Watts (max.)
Temperature	 Operating: 0° ~ 40°C (32° ~ 104°F) Storage: -20° ~ 70°C (-4° ~ 158°F)
Humidity	Max. 90% (non-condensing)
Certifications	CE, FCC, HomePlug® AV

200Mbps Powerline AV Adapter Kit with Bonus Outlet TPL-307E2K (V1.0R)



NETWORKING SOLUTIONS



PACKAGE CONTENTS

2 x TPL-307E

Multi-Language Quick Installation Guide

CD-ROM (Utility & User's Guide)

2 x network cables (1.5 m / 5 ft.)

RELATED PRODUCTS

TEW-692GR	450Mbps Concurrent Dual Band Wireless N Router
TPL-306E2K	200Mbps Compact Powerline AV Adapter Kit
TPL-402E2K	500Mbps Powerline AV Adapter Kit with Bonus Outlet

CONTACT INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com 1-888-326-6061

