





# 4-Port USB 3.0 Hub

# TU3-H4 (v1.1R)

TRENDnet's 4-Port USB 3.0 Hub provides four super speed USB 3.0 ports to connect flash drives, storage enclosures, cameras, and other USB 3.0 devices to your computer.

With no drivers required, simply plug into any free USB 3.0 port on your PC or Mac to experience the time savings of transferring data at 5Gbps, 10 times faster than USB 2.0 speeds.

Simply connect to an available USB port on your computer with the included USB 3.0 cable (backward compatible with USB 2.0). Upgrade to super speed USB 3.0 with TRENDnet's TU3-H2EC or TU3-H2PIE. An included power adapter ensures proper operability of power hungry bus-powered connected devices.

# **FEATURES**

- Transfer data at super speeds of 5Gbps with USB 3.0
- 4 x USB 3.0 Type A super speed ports
- USB Type A ports are backwards compatible with USB 2.0, 1.1, and 1.0 devices
- 1 x USB 3.0 Type B super speed port (connection to computer)
- 1 x power port
- 1 x USB 3.0 Type A to Type B cable (1.8 m / 6 ft.)
- Included power adapter fully powers connected devices
- · LED indicators convey port activity
- Use with TRENDnet's TU3-H2EC or TU3-H2PIE
- · Compact size and shape
- Easy Plug and Play installation
- Works with most operating systems\*\*
- · 2-year limited warranty

\*Data is transferred over USB 3.0 connections at up to 5Gbps. However actual data throughput may be significantly affected by choice of hard drive, computer system architecture, CPU loading, and other factors

\*\*USB 3.0 super speeds are based on compatible operating systems. USB 3.0 is backwards compatible with USB 2.0 and will work on all compatible operating systems


# **4-Port USB 3.0 Hub** TU3-H4 (v1.1R)



### **SPECIFICATIONS**

HARDWARE	
Standard	USB 3.0 (Backwards compatible USB 2.0, 1.1, and 1.0)
Ports	<ul> <li>Input: 1 x Type–B</li> <li>Output: 4 x Type A</li> <li>1 x power port</li> </ul>
Power Supply	• 5V DC / 2.5A
Power Consumption	• 0.3 W
Dimension	• 60 x 95 x 22 mm (2.3 x 3.7 x 0.8 in.)
Weight	• 68 g (2.4 oz)
Temperature	• Operating: 0° ~ 40°C (32° ~ 104°F) • Storage: -10°C ~ 85°C (14° ~ 185° F)
Humidity	Max. 90% non-condensing
Certifications	• CE, FCC

#### **NETWORKING SOLUTIONS**



#### PACKAGE CONTENTS

TU3-H4
Multi-Language Quick Installation Guide
USB 3.0 Type A to Type B cable (1.8 m / 6 ft.)
Power adapter (5V DC, 2.5A)

## RELATED PRODUCTS

TU3-S35	3.5" USB 3.0 External Enclosure
TU3-H2PIE	2-Port USB 3.0 PCI Express Adapter
TU3-H2EC	2-Port USB 3.0 ExpressCard Adapter

#### CONTACT INFORMATION

#### TRENDIET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

1-888-326-6061