



## SecurView Wireless N Day/Night Internet Camera TV-IP312WN (V1.0R)

The SecurView Wireless N Day/Night Internet Camera, transmits high quality video and audio over the Internet. Wireless n technology provides unsurpassed wireless coverage and improved streaming video quality.

Add this camera to your wireless network at the touch of a button with Wi-Fi Protected Setup (WPS). Infrared bulbs provide night vision for distances of up to five meters (16 feet) in complete darkness. A built-in microphone and optional speakers accommodate 2-way audio communications. Manage up to 32 SecurView cameras with the included complimentary camera management software.

Advanced features include motion detection recording, email alerts, scheduled recording sessions, MPEG-4 / MJPEG image compression, and digital zoom. A wall/ceiling mounting kit is included and the off-white camera housing blends into most environments.

## FEATURES

- Wi-Fi compliant with IEEE 802.11b/g/n networks
- 3 x digital zoom
- 1 x 10/100Mbps Fast Ethernet port
- 1 x Wi-Fi Protected Setup button
- 1 x USB port to store still images to a USB flash drive\*
- High quality MPEG-4 and MJPEG video recording with up to 30 frames per second
- Resolution up to 640 x 480 pixels
- Power and activity LED indicators (can be disabled)
- Infrared night vision for up to 5 meters (16 feet)
- Dynamic DNS support
- Image control: brightness, contrast, saturation, and mirror (horizontally/vertical)
- Supports TCP/IP networking, SMTP Email, HTTP, Samba, and other Internet protocols
- Record streaming video to your computer and Network Storage Server
- Motion detection triggered email alerts and image upload via FTP
- Stream Internet camera video to a 3GPP compatible mobile device
- Supports 64/128-bit WEP and WPA/WPA2-PSK wireless encryption
- Hear and talk to people in your camera's viewing area through your computer
- Two adjustable motion detection windows with just-in-time snapshot
- Quick Universal Plug and Play installation
- Complimentary SecurView Pro software: manage up to 32 camera\*\*
- 3-year limited warranty

\* USB port supports up to 500mA powered device with FAT16/32 format

\*\* Monitoring multiple cameras may require a high performance CPU

# SecurView Wireless N Day/Night Internet Camera

TV-IP312WN (V1.0R)



## SPECIFICATIONS

### CAMERA

|                          |   |
|--------------------------|---|
| <b>General</b>           | <ul style="list-style-type: none"><li>• Sensor: 1/4" color CMOS sensor</li><li>• Resolution: 640 x 480 pixels</li><li>• Board Lens</li><li>• Focal Length: 4.5mm</li><li>• Aperture (F/No): F2.8</li><li>• Aperture (F/No): F2.8</li><li>• Minimum illumination: 0 Lux</li><li>• Diagonal viewing angle: 60 degree</li></ul>        |
| <b>Image &amp; Video</b> | <ul style="list-style-type: none"><li>• Compression: MPEG-4/MJPEG dual streaming</li><li>• Exposure/white balance/gain control : automatic</li><li>• Resolution: up to 30fps for VGA (640x480), 30fps for QVGA (320x240), 30fps for QQVGA (160x120)</li></ul>   |
| <b>Audio</b>             | <ul style="list-style-type: none"><li>• Audio in: internal omni-directional microphone</li><li>• Sensitivity: -48dB +/- 3dB</li><li>• Frequency response: 50 ~ 16000Hz</li><li>• Audio out: external output to active speaker (mono)</li><li>• Echo Cancellation: hardware voice processor</li><li>• Audio codec: PCM/AMR</li></ul> |

### HARDWARE

|                          |  |
|--------------------------|--|
| <b>Network</b>           | <ul style="list-style-type: none"><li>• IEEE 802.3u 10/100Mbps Fast Ethernet, Auto-MDIX</li></ul>  |
| <b>LED</b>               | <ul style="list-style-type: none"><li>• Power, Link</li></ul>  |
| <b>USB Port</b>          | <ul style="list-style-type: none"><li>• Type A USB 1.1 host port</li></ul>   |
| <b>Reset Button</b>      | <ul style="list-style-type: none"><li>• Restore to factory default</li></ul>   |
| <b>WPS Button</b>        | <ul style="list-style-type: none"><li>• Push button for Wi-Fi Protected Setup</li></ul>  |
| <b>Power Consumption</b> | <ul style="list-style-type: none"><li>• 8 watts max.</li></ul>   |
| <b>Power</b>             | <ul style="list-style-type: none"><li>• 5 V, 2.5 A external power adapter</li></ul>  |
| <b>Dimension</b>         | <ul style="list-style-type: none"><li>• 70 x 100 x 57 mm (2.67 x 3.94 x 2.95 in.)</li></ul>  |
| <b>Weight</b>            | <ul style="list-style-type: none"><li>• 155 g (5.4 oz)</li></ul>   |
| <b>Temperature</b>       | <ul style="list-style-type: none"><li>• Operating: 0° C ~ 45° C (32°F ~ 113° F)</li><li>• Storage: -15° C ~ 60° C (5°F ~ 140° F)</li></ul> |
| <b>Humidity</b>          | <ul style="list-style-type: none"><li>• Max. 90% (non-condensing)</li></ul>  |
| <b>Certifications</b>    | <ul style="list-style-type: none"><li>• CE, FCC</li></ul>  |

### REQUIREMENTS

|                             |  |
|-----------------------------|--|
| <b>Management Interface</b> | <ul style="list-style-type: none"><li>• Internet Explorer 6.0 or above</li></ul>   |
| <b>To Run SecurView Pro</b> | <ul style="list-style-type: none"><li>• Windows 7 (32/64 bit), Vista (32/64 bit), XP (32/64 bit)</li></ul>   |
| <b>SecurView Pro</b>        | <ul style="list-style-type: none"><li>• Channel: supports up to 32 cameras</li><li>• Record/Playback/Motion Detection</li></ul>                    |
| <b>Network Protocols</b>    | <ul style="list-style-type: none"><li>• TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP and RTCP</li></ul> |

### WIRELESS

|                                  |   |
|----------------------------------|---|
| <b>Standard</b>                  | <ul style="list-style-type: none"><li>• Based on IEEE 802.11n technology</li><li>• IEEE 802.11g/b compliant</li></ul>                                     |
| <b>Frequency</b>                 | <ul style="list-style-type: none"><li>• 2.4 ~ 2.4835GHz</li></ul>   |
| <b>Antenna</b>                   | <ul style="list-style-type: none"><li>• 1 x 2dBi dipole antenna (Reverse-SMA connector)</li></ul>   |
| <b>Data Rate (auto fallback)</b> | <ul style="list-style-type: none"><li>• 802.11n: up to 150Mbps</li><li>• 802.11g: up to 54Mbps</li><li>• 802.11b: up to 11Mbps</li></ul>                  |
| <b>Security</b>                  | <ul style="list-style-type: none"><li>• 64/128-bit WEP, WPA/WPA2-PSK</li></ul>  |
| <b>Output Power</b>              | <ul style="list-style-type: none"><li>• 802.11n: 15 + 1 dBm</li><li>• 802.11b: 15 + 1 dBm</li><li>• 802.11g: 18 + 1 dBm</li></ul>                         |
| <b>Receiving Sensitivity</b>     | <ul style="list-style-type: none"><li>• 802.11n HT20: -67dBm</li><li>• 802.11n HT40: -64dBm</li><li>• 802.11g: -70dBm</li><li>• 802.11b: -87dBm</li></ul> |
| <b>Channel</b>                   | <ul style="list-style-type: none"><li>• 1~11 (FCC), 1~13 (ETSI)</li></ul>   |

### MANAGEMENT

|                         |   |
|-------------------------|---|
| <b>Remote</b>           | <ul style="list-style-type: none"><li>• Remote management supported</li></ul>       |
| <b>Backup / Restore</b> | <ul style="list-style-type: none"><li>• Save/retrieve configuration files</li></ul> |

# SecurView Wireless N Day/Night Internet Camera

## TV-IP312WN (V1.0R)



### SPECIFICATIONS

#### SETTINGS

|                      |   |
|----------------------|---|
| <b>Recording</b>     | <ul style="list-style-type: none"><li>Recording type: continuous, schedule or motion detection with software</li></ul>                            |
| <b>Image</b>         | <ul style="list-style-type: none"><li>Brightness, sharpness, saturation, flip, mirror, (horizontal/vertical)</li></ul>                            |
| <b>Video</b>         | <ul style="list-style-type: none"><li>Encoding type: Resolution:640x480, 320x240,160x120 • Frame rate: 1~30 fps • Compression: 5 levels</li></ul> |
| <b>Multi-Profile</b> | <ul style="list-style-type: none"><li>3 profiles simultaneously</li></ul>   |
| <b>Port Settings</b> | <ul style="list-style-type: none"><li>HTTP port: 80 (default)</li></ul>   |
| <b>Digital Zoom</b>  | <ul style="list-style-type: none"><li>3x</li></ul>  |
| <b>Dynamic DNS</b>   | <ul style="list-style-type: none"><li>Yes</li></ul>   |
| <b>Time</b>          | <ul style="list-style-type: none"><li>Synchronize with NTP server or set time/date manually</li></ul>   |
| <b>SMTP</b>          | <ul style="list-style-type: none"><li>SMTP mail supported up to 2 accounts with software</li></ul>  |
| <b>System Log</b>    | <ul style="list-style-type: none"><li>100 entries (max.)</li></ul>  |

### NETWORKING SOLUTIONS



### PACKAGE CONTENTS

|   |
|---|
| TV-IP312WN                              |
| Multi-Language Quick Installation Guide |
| CD-ROM (Utility & User's Guide)         |
| Power adapter (5V DC, 2.5 A)            |
| Network cable (1.8 m/5.9 ft.)           |
| Mounting stand                          |

### RELATED PRODUCTS

|                   |  |
|-------------------|--|
| <b>TV-IP121WN</b> | SecurView Wireless N Day/Night Internet Camera               |
| <b>TV-IP252P</b>  | SecurView PoE Dome Internet Camera                           |
| <b>TV-IP422WN</b> | SecurView Wireless N Day/Night Pan/Tilt/Zoom Internet Camera |

### CONTACT INFORMATION



20675 Manhattan Place, Torrance, CA 90501 USA  
Tel: 1-310-961-5500  
Fax: 1-310-961-5511  
Web: [www.trendnet.com](http://www.trendnet.com)  
Email: [sales@trendnet.com](mailto:sales@trendnet.com)  
**1-888-326-6061**

