



Wireless N Internet Camera TV-IP551W (v1.0R)

The Wireless N Internet Camera, model TV- IP551W, transmits real-time video over the Internet. Wireless n technology provides unsurpassed wireless coverage and improved streaming video quality. Add this camera to your wireless network at the touch of a button with Wi-Fi Protected Setup (WPS).

Record 640 x 480 (VGA) video at up to 20 frames per second (fps). Manage up to 32 TRENDnet cameras with the included complimentary camera management software. Advanced features include adjustable motion detection recording areas, email alerts, scheduled recording sessions, one-way audio, an adjustable lens, and four times digital zoom. A wall / ceiling mounting kit is included and the camera's off white housing blends into most environments.

PRODUCT OVERVIEW

- See video from any Internet connection
- High speed wireless n connection
- Program motion detection recording, recording schedules, email alerts and more with complimentary software
- One-way audio
- Wall / ceiling mounting kit



FEATURES

- Wi-Fi compliant with IEEE 802.11n standard
- Backwards compatible with IEEE 802.11g and IEEE 802.11b devices
- One touch WPS connection button
- 1 x 10/100Mbps Auto-MDIX RJ-45 port (for optional wired installation)
- Power and activity LED indicators (can be disabled)
- 1-way audio
- Reset button
- 4x digital zoom
- Dynamic DNS support
- Supports up to 640 x 480 pixel MJPEG resolution at up to 20 frames per second
- Image controls: Brightness, contrast, saturation, flip image vertically, mirror image horizontally
- Define a recording schedule or motion detection recording
- Create motion detection fields over the viewing area
- Supports TCP/IP networking, Email, HTTP, and other Internet protocols
- System controls:
 - Define up to 64 user login accounts
 - Set the date and time or synchronize with an NTP server
- Supports wireless encryption up to WPA2-PSK
- Quick Universal Plug and Play (UPnP) installation
- Complimentary TRENDnetVIEW Pro software: manage up to 32 cameras *
- TRENDnetVIEW Pro software compatible with Windows operating systems
- Mounting base and mounting hardware included
- 3-year limited warranty

*Monitoring multiple cameras may require a high performance CPU



TRENDNETVIEW PRO CAMERA SOFTWARE FEATURES

- Manage up to 32 cameras
- Compatible with Windows and Microsoft Server 2008
- Multiple language support
- Camera Viewing
 - Preset viewing modes
 - Program custom viewing modes
 - Full screen view
 - Drag and drop live feeds to a new location
 - Program camera cycle viewing sequence
 - Motion detection brings video forward
 - Side, top, and bottom tool bars can be hidden
 - Web based access from smart phones and tablets
- Recording options
 - Program weekly recording schedules
 - Motion detection recording
 - Define motion detection areas of any shape
 - Define motion detection sensitivity
 - Event trigger recording
 - Date and time overlay
 - Save a single video stream to multiple locations simultaneously
 - Define recording quotas by recording time or space allocation
 - Disk clean feature condenses and optimizes old files
 - Real time recording stats to help manage files
- Search and Playback
 - Navigation timeline provides a quick visual reference to the recorded content
 - Search continuous recordings by motion
 - Search recordings by motion within a defined field (a portion of the viewing area)
 - Time laps playback search
- Map cameras on an image such as a floor plan
- Map cameras on Google Maps™

SPECIFICATIONS

CAMERA

General	<ul style="list-style-type: none"> • Sensor: 1/5" CMOS Sensor • Board Lens • Focal Length: 4 mm • F/No: 1.5 • Minimum illumination: 1 lux • Focus Depth: 20 cm ~ infinity • View: <ul style="list-style-type: none"> • Horizontal: 38 degrees • Vertical: 28.7 degrees • Diagonal: 46.5 degrees • Digital Zoom: 4x
Audio	<ul style="list-style-type: none"> • Built-in omni-directional microphone • Sensitivity: -38dB +/- 3dB (5 meters max) • Frequency: 100~20000Hz • S/N: >60dB • Format: PCM

HARDWARE

Network	<ul style="list-style-type: none"> • IEEE 802.3u 10/100 Mbps Auto-MDIX Fast Ethernet
LED	<ul style="list-style-type: none"> • Power, Link/Act
WPS Button	<ul style="list-style-type: none"> • Enable WPS connection
Power Consumption	<ul style="list-style-type: none"> • 5 watts max.
Power	<ul style="list-style-type: none"> • Input: 100~240V, 50/60Hz, 0.2A • Output: 5V, 1.2A external power adapter
Dimension	<ul style="list-style-type: none"> • 75 x 115 x 30 mm (2.95 x 4.5 x 1.2 in.)
Weight	<ul style="list-style-type: none"> • 110 g (3.8 oz.)
Temperature	<ul style="list-style-type: none"> • Operating: 0°C ~ 40°C (32°F ~ 104°F) • Storage: -15°C ~ 60°C (5°F ~ 140°F)
Humidity	<ul style="list-style-type: none"> • Max. 95% (non-condensing)
Certifications	<ul style="list-style-type: none"> • CE, FCC

REQUIREMENT

Management Interface	<ul style="list-style-type: none"> • Internet Explorer 7.0 or higher • Firefox 3.5 or above • Safari 4.0 or above
To Run software	<ul style="list-style-type: none"> • Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit) • Windows Server 2003, 2008
TRENDnetView Pro Software	<ul style="list-style-type: none"> • Channel: supports up to 32 cameras • Record / Playback / Motion Detection / Audio
Network Protocols	<ul style="list-style-type: none"> • IPv4, ARP, TCP, UDP, ICMP • DHCP Client, NTP Client, DNS Client, DDNS Client, SMTP Client, FTP Client • HTTP • PPPoE • UPnP

WIRELESS

Standard	<ul style="list-style-type: none"> • IEEE 802.11b, IEEE 802.11g, and IEEE 802.11n
Frequency	<ul style="list-style-type: none"> • 2.4 ~ 2.497 GHz ISM band
Modulation	<ul style="list-style-type: none"> • DQPSK, DBPSK, DSSS and CCK
Antenna	<ul style="list-style-type: none"> • Built-in 2dBi antenna



SPECIFICATIONS

WIRELESS

Date Rate	<ul style="list-style-type: none">• 802.11b: up to 11Mbps• 802.11g: up to 54Mbps• 802.11n: up to 150Mbps
Security	<ul style="list-style-type: none">• 64/128-bit WEP, WPA / WPA2-PSK
Output Power	<ul style="list-style-type: none">• 802.11b: 17dBm (typical)• 802.11g: 14.5dBm (typical)• 802.11n: 14.5dBm (typical)
Receiving Sensitivity	<ul style="list-style-type: none">• 802.11b: -89dBm at 11Mbps• 802.11g: -74dBm at 54Mbps• 802.11n: -71dBm at 150Mbps
Channels	<ul style="list-style-type: none">• 1~11 (FCC), 1~13(ETSI)

MANAGEMENT

Accounts	<ul style="list-style-type: none">• Up to 64 user accounts
Remote Login	<ul style="list-style-type: none">• Remote management supported
Backup / Restore	<ul style="list-style-type: none">• Save / retrieve configuration files

SETTINGS

Image	<ul style="list-style-type: none">• Brightness, contrast, saturation, flip, mirror (horizontal / vertical)
Video Setting	<ul style="list-style-type: none">• Encoding: MJPEG<ul style="list-style-type: none">• Resolution: 640 x 480, 320 x 240, 160 x 120• Max frame rate: VGA @ 20fps, QVGA @ 30fps, QQVGA @ 30fps• JPEG quality: Very Low, Low, Medium, High, Very High
Recording	<ul style="list-style-type: none">• Event based (motion detection) and scheduled
Snapshot	<ul style="list-style-type: none">• Trigger event: motion detection• Action: send alert email and / or upload to FTP• Real time snapshot
Port Settings	<ul style="list-style-type: none">• HTTP port: 80 (default)
Time	<ul style="list-style-type: none">• Synchronize with NTP server or set time / date manually

Wireless N Internet Camera TV-IP551W (v1.0R)



NETWORKING SOLUTIONS



PACKAGE CONTENTS

TV-IP551W

CD-ROM (Utility & User's Guide)

Multi-Language Quick Installation Guide

Network cable (1.5 m / 5 ft.)

Power adapter (5V DC, 1.2A)

Camera mounting kit

RELATED PRODUCTS

TV-IP551WI	Wireless N Day / Night Internet Camera
TV-IP572W	Megapixel Wireless N Internet Camera
TV-IP672W	Megapixel Wireless N PTZ Internet Camera

CONTACT INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

1-888-326-6061

