



Megapixel HD PoE PTZ Internet Camera TV-IP672P (V1.0R)

The Megapixel HD PoE PTZ Internet Camera, model TV-IP672P, provides video monitoring over a large area. Pan the camera side-to-side a remarkable 340° and tilt up-and-down 115° from any Internet connection. No need to install this camera near a power source, power and data are received through a single Ethernet cable using Power over Ethernet (PoE) technology (See TRENDnet PoE Switches and Injectors).

Record 1280 x 800 Megapixel (WXGA) video at up to 30 frames per second (fps). Manage up to four video profiles to record HD video while streaming low resolution video to a compatible smart phone at the same time. Manage up to 32 TRENDnet cameras with the included complimentary camera management software. Advanced features include adjustable motion detection recording areas, email alerts, scheduled recording sessions, pan / tilt, Auto-Patrol, H.264 / MPEG-4 / MJPEG image compression, date-and-time overlays, a Micro-SD card slot for backup storage, two-way audio (speakers not included), an adjustable lens, and four times digital zoom. A wall / ceiling mounting kit is included and the camera's off white housing blends into most environments.

PRODUCT OVERVIEW

- See more with Megapixel resolution up to 1280 x 800 (WXGA)
- Pan 340° side-to-side and tilt 115° up-and-down
- No need to install this camera near a power source, power and data are received through a single Ethernet cable
- Program motion detection recording, recording schedules, email alerts and more with complimentary software
- 2-way audio

FEATURES

- 1 x 10/100 Mbps Auto-MDIX RJ-45 PoE port
- Power and activity LED indicators (can be disabled)
- 2-way audio: built-in microphone and audio out port for third party speakers
- 4x digital zoom
- Micro SD card slot*
- Manual focus lens
- Stream and record up to 4 different video profiles simultaneously
- Pan left or right 170° for a total of 340°
- Tilt the camera up 90° and down 25° for a total of 115°
- Stream Internet camera video to a 3GPP compatible wireless device
- Dynamic DNS support
- Supports up to 1280 x 800 pixel resolution at up to 30 frames per second
- Image controls: brightness, contrast, auto gain control, noise reduction, saturation, sharpness, back light control, hue, frequency, flip image vertically, mirror image horizontally, and black and white mode
- Event Trigger: motion detection or digital input signal
- Event Action: send real-time snapshots (up to 3 before and 3 after the event) or video recording (up to 5 seconds before and 10 seconds after the event) to FTP or email
- Samba client support to record to a NAS drive
- Supports TCP/IP networking, email, HTTP, Samba and other Internet protocols
- System controls:
 - Define up to 20 user login accounts
 - Set the date and time or synchronize with an NTP server
- Quick Universal Plug and Play (UPnP) installation
- Mounting base and mounting hardware included
- 3-year limited warranty

* Micro SD card sold separately

TRENDNETVIEW PRO CAMERA SOFTWARE FEATURES

- Manage up to 32 cameras
- Compatible with Windows and Microsoft Server 2008
- Multiple language support
- Camera Viewing
 - Preset viewing modes
 - Program custom viewing modes
 - Full screen view
 - Drag and drop live feeds to a new location
 - Program camera cycle viewing sequence
 - Motion detection brings video forward
 - Side, top, and bottom tool bars can be hidden
 - Web based access from smart phones and tablets
- Recording options
 - Program weekly recording schedules
 - Motion detection recording
 - Define motion detection areas of any shape
 - Define motion detection sensitivity
 - Event trigger recording
 - Date and time overlay
 - Save a single video stream to multiple locations simultaneously
 - Define recording quotas by recording time or space allocation
 - Disk clean feature condenses and optimizes old files
 - Real time recording stats to help manage files
- Search and Playback
 - Navigation timeline provides a quick visual reference to the recorded content
 - Search continuous recordings by motion
 - Search recordings by motion within a defined field (a portion of the viewing area)
 - Time lapse playback search
- Map cameras on an image such as a floor plan
- Map cameras on Google Maps™

SPECIFICATIONS

CAMERA

General	<ul style="list-style-type: none"> • Sensor: 1/4" CMOS Sensor • Board Lens • Focal Length: 4 mm • F/No: 1.5 • Minimum illumination: 1 lux • Focus Depth: 20 cm ~ infinity • View: <ul style="list-style-type: none"> • Horizontal: 51.8° • Vertical: 33.8° • Diagonal: 59.6° • Digital Zoom: 4x
Audio	<ul style="list-style-type: none"> • Built-in omni-directional microphone • Sensitivity: -40 dB +/- 3 dB (5 meters max) • Frequency: 100~20000 Hz • S/N: >60 dB • Format: PCM / ADPCM • External speaker output (speaker sold separately) • Two-way audio
Pan & Tilt	<ul style="list-style-type: none"> • Pan: - 170° ~ + 170° • Tilt: up 90° and down 25° • Auto-Patrol preset positions: 10

HARDWARE

Network	<ul style="list-style-type: none"> • IEEE 802.3u 10/100 Mbps Auto-MDIX Fast Ethernet • IEEE 802.3af Power over Ethernet (PoE)
LED	<ul style="list-style-type: none"> • Power, Link/Act
Reset Button	<ul style="list-style-type: none"> • Reset to factory default
Privacy Button	<ul style="list-style-type: none"> • Privacy mode on / off
Power Consumption	<ul style="list-style-type: none"> • Max 9 Watts
Power	<ul style="list-style-type: none"> • Input: 100~240V, 50/60 Hz, 0.5A • Output: 12V, 1.25A external power adapter
Dimension	<ul style="list-style-type: none"> • 113 x 113 x 130 mm (4.5 x 4.5 x 5.1 in.)
Weight	<ul style="list-style-type: none"> • 495 g (1.1 lbs.)
Temperature	<ul style="list-style-type: none"> • Operating: 0°C ~ 40°C (32°F ~ 104°F) • Storage: -25°C ~ 70°C (-13°F ~ 158°F)
Humidity	<ul style="list-style-type: none"> • Max 90% (non-condensing)
Certifications	<ul style="list-style-type: none"> • CE, FCC

REQUIREMENT

Management Interface	<ul style="list-style-type: none"> • Internet Explorer 7.0 or above • Firefox, Safari 4 - 8, and Chrome
To Run software	<ul style="list-style-type: none"> • Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit) • Windows Server 2003, 2008
TRENDnetVIEW Pro Software	<ul style="list-style-type: none"> • Channel: supports up to 32 cameras • Record / Playback / Motion Detection / Audio

SPECIFICATIONS

REQUIREMENT

Network Protocols	<ul style="list-style-type: none"> • IPv4, ARP, TCP, UDP, ICMP • DHCP Client, NTP Client, DNS Client, DDNS Client, SMTP Client, FTP Client • HTTP • Samba Client • PPPoE • UPnP • LLTD • RTP (Real Time Protocol) • RTCP (Real Time Control Protocol) • RTSP (Real Time Streaming Protocol) • 3GPP (video only)
--------------------------	--

MANAGEMENT

System	<ul style="list-style-type: none"> • Web based administration
Access	<ul style="list-style-type: none"> • Up to 20 user accounts
Backup / Restore	<ul style="list-style-type: none"> • Save / retrieve configuration files
Log	<ul style="list-style-type: none"> • System log up to 500 entries
Micro SD	<ul style="list-style-type: none"> • View, download, delete files • Format and remove Micro SD card (SDHC, up to 32 GB)

MANAGEMENT

Image	<ul style="list-style-type: none"> • Brightness, contrast, saturation, sharpness, white balance, flip, mirror (horizontal / vertical), black & white, indoor, outdoor, schedule mode • Shutter: 1/3.25s, 1/7.5s, 1/10s, and 1/15s
Video Setting	<ul style="list-style-type: none"> • Profile 1: H.264 / MPEG-4 <ul style="list-style-type: none"> • Resolution: 1280 x 800, 640 x 400, 320 x 192, 160 x 96 • Max frame rate: 30fps • Profile 2: H.264 / MPEG-4 <ul style="list-style-type: none"> • Resolution: 640 x 400, 320 x 192, 160 x 96 • Max frame rate: 30fps • Profile 3: MJPEG <ul style="list-style-type: none"> • Resolution: 1280 x 800, 640 x 400, 320 x 192, 160 x 96 • Max frame rate: 1280 x 800 @ 5fps, 640 x 400 / 320 x 192@30fps • JPEG quality: Low, Fair, Standard, Good, Excellent • Profile 4: H.264 / MPEG-4 <ul style="list-style-type: none"> • Resolution: 640 x 400, 320 x 192, 160 x 96 • Max frame rate: 30fps • RTSP: http://ipcamera_ip/3gpp
3GPP	<ul style="list-style-type: none"> • Audio format: AMR • Video format: MPEG-4 • Protocols: RTSP, RTP, RTCP
Recording	<ul style="list-style-type: none"> • Resolution: Define individual resolution for up to 4 profiles • Required storage: 32 MB (minimum per profile) • Recording type: event based (motion detection), continuous, and scheduled
Event Action	<ul style="list-style-type: none"> • Trigger event: motion detection • Action: send real-time snapshot or video recording to FTP or email
Port Settings	<ul style="list-style-type: none"> • HTTP port: 80 (default) • RTSP port: 554 (default)
Time	<ul style="list-style-type: none"> • Synchronize with NTP server or set time / date manually

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TV-IP672P
- CD-ROM (Utility & User's Guide)
- Multi-Language Quick Installation Guide
- Network cable (1.5 m / 5 ft.)
- Power adapter (12V, 1.25A)
- Camera mounting kit

RELATED PRODUCTS

TV-IP672PI	Megapixel PoE Day / Night PTZ Internet Camera
TV-IP651W	Wireless N PTZ Internet Camera
TV-IP572WI	Megapixel Wireless N Day / Night Internet Camera

CONTACT INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com
1-888-326-6061