

TV-IP862IC / TV-IP562WI / TV-IP662PI / TV-IP662WI

Camera Firmware Upgrade Procedures

Warning:

- Always upgrade firmware with a wired connection.
- Do not interrupt the connection while doing the firmware upgrading
- Save your configuration before firmware upgrade

Note:

- 1) TV-IP862IC is used for procedures below; other cameras follow the similar route.
- 2) It is necessary to perform a factory reset after the firmware upgrade. If you would like to keep your original setting, please back up your configuration first prior to upgrade the firmware as instructed at the last page.

Firmware Upgrade


1. Download and unzip the firmware file from www.trendnet.com/downloads . Save the firmware on your computer. The firmware file name ends with *.bin.
2. Open a browser and go to your camera's IP address: to find the camera IP, please use the Setup Wizard, on the CD-ROM (default is 192.168.10.30, without a DHCP server.)




3. Enter the username & password (By default, the username & password is admin/admin, or enter the password setup by you.)




- Go to **Tools** page, then **Firmware Upgrade** option, and click **Browse** to select the new firmware file then click **Upload**. If you would like to keep your original setting, please back up your configuration prior to upgrade the firmware as instructed at the last page.




- Firmware upgrade completed.




- Go to **Tool** and under the **System** to **Reboot** the camera and it may take up to 2 minutes till completed.



- After firmware upgrade, under **Tool/System** please click **factory reset**



8. After reset, click **Tool/Firmware Upgrade** tab again to check the new firmware version. Also after reset, the user name and password would become the default admin, admin.



9. Your firmware upgrade is now completed. To find the camera IP, please use the Setup Wizard (can be found on the CD-ROM) to search and configure your camera again.

10. **Back up**

To keep your original settings prior to the firmware upgrade, please **back up** the config.cfg file and save the file to your chosen folder before the firmware upgrade starts.

Restore

After the firmware upgrade and factory reset completed, then **Restore** the config.cfg file and your original settings will be restored.

