

TE100-PCIFXplus **100Base-FX SC Connector PCI Fast Ethernet Fiber Adapter**

The PCI Fiber Optic Adapter operates in a 32-bit Bus Master Mode, delivering 100Mbps of speed with little stress on the host's CPU. The TE100-PCIFXplus supports both half- and full-duplex modes, creating an increase speed up to 200Mbps. With its SC-type fiber connection allowing up to 2Km away from the switch, TRENDnet's TE100-PCIFXplus is the perfect choice for greater bandwidth and long cable connections in the network



FEATURES

- ...> Complies with IEEE 802.3 μ 100Base-FX standard
- ...> Meets PCI Specification Rev. 2.2
- ...> 32-bit PCI Bus Master operation
- ...> 100Mbps Fast Ethernet connection
- ...> Supports half- and full-duplex modes
- ...> Supports 2Km fiber cable long transfer distance
- ...> Auto-assignment of IRQ and I/O address
- ...> Easy-to-view diagnostic LEDs
- ...> Supports Wake-On-LAN (WOL). 3-wire WOL cable included
- ...> Supports Desktop Management Interface (DMI)
- ...> 5-Year Warranty

BENEFITS

- ...> **Performance:**
Operates in the 32-bit bus master mode, and transfers data directly to/from the host's memory.
- ...> **Expandability:**
Uses standard SC type fiber connector for easy and reliable connection.
- ...> **Flexibility:**
Supports all major network operating systems.
- ...> **Reliability:**
With 100/200Mbps speeds, our TE100-PCIFXplus offers a lifetime warranty.



TE100-PCIFXplus

100Base-FX SC Connector PCI Fast Ethernet Fiber Adapter

SPECIFICATIONS

Standards:

- IEEE 802.3 μ 100Base-FX

Data Transfer Rate:

- 100Mbps (half-duplex) / 200Mbps (full-duplex)

Protocol:

- CSMA/CD

Connectors:

- Multimode SC fiber connector

Diagnostic LEDs:

- Link and Activity

Network Drivers:

- Novell Netware 3.x/4.x, ODI driver, NetWare Client 32, Windows for Workgroups, Windows 95/98/2000/NT/XP, IBM OS/2 Warp Server, Linux, NDIS driver, and other major network operating systems

Power Consumption:

- 5 VDC, 700mA Max.

Dimensions:

- 135 x 121 mm (5.31 x 4.76 inches)

Weight:

- 85 g (3 oz)

Temperature:

- Operating: 0° to 40° C (32° F to 104° F)
- Storage: -25° to 70° C (-13°F to 158° F)

Humidity:


- 10 % to 90 % (non-condensing)

Certifications:

- FCC, CE, VCC1



NETWORKING SOLUTIONS



To Order Please Call:
1-888-326-6061

RELATED PRODUCT

- **TE100-PCIFXplus:**
100Base-FX Fast Ethernet Fiber Adapter for PCI
- **TE100-S88FX:**
8-Port 100Base-FX Fast Ethernet Switch
- **TE100-S86FX:**
8-port (6 x 100Base-FX, 2 x 10/100Mbps) Fast Ethernet Switch
- **TE100-S81FX:**
6-port (1 x 100Base-FX, 7 x 10/100Mbps) Fast Ethernet Switch
- **TE100-TF:**
100Base-TX to 100Base-FX SC-type converter

ORDERING INFORMATION

TRENDware International, Inc.
3135 Kashiwa Street
Torrance, CA. 90505. USA
Tel: 310-891-1100
Fax: 310-891-1111
Web: www.TRENDNET.com
Email: sales@trendware.com

