


5-Port Unmanaged 2.5G Switch

TEG-S350 (v1.1R)


- 5 x 2.5GBASE-T ports
- IEEE 802.3bz (2.5G) compliant
- Backwards compatible with 10/100/1000Mbps devices
- 25Gbps switching capacity
- Fanless design eliminates noise
- Wall mountable for installation flexibility
- Lifetime Warranty
- NDAA / TAA compliant (U.S. and Canada only)

Expand your network's bandwidth and reduce digital bottlenecks with TRENDnet's Unmanaged 2.5G Switches. These 2.5G network switches come equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over your existing Cat5e or better cabling. Each high-speed 2.5G switch features a durable metal enclosure and can be mounted to the wall for setup flexibility. The fanless design lowers energy consumption and eliminates distracting operating noise. TRENDnet's reliable 2.5G switches are cost-effective solutions to increase your network's throughput.




2.5G Ports

Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling.



Wall Mountable


The 2.5G switches feature metal housing with a convenient wall mountable design for greater installation flexibility.



Fanless


The fanless design of the 2.5G switches lowers energy consumption costs and eliminates operating noise.

NETWORKING SOLUTION



FEATURES

- 1** **2** **3** **Easy Installation**
No configuration needed, simply connect network devices to the 2.5G Ethernet switch
- 2.5G Ports**
Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling
- Fanless**
Fanless design lowers energy consumption and eliminates operating noise
- Housing Design**
Sturdy metal housing
- Wall Mountable**
Features a convenient wall mountable design for greater installation flexibility
- Jumbo Frame**
Sends larger packets, or Jumbo Frames (up to 12KB) for increased performance
- LED Indicators**
LED indicators on this 2.5G switch conveys port status



SPECIFICATIONS

Standards

- IEEE 802.3x
- IEEE 802.3z
- IEEE 802.3ab
- IEEE 802.3az
- IEEE 802.3bz

Device Interface

- 5 x 2.5GBASE-T ports (1Gbps/ 2.5Gbps)
- LED indicators

Data Transfer Rate

- Gigabit: 2000Mbps (full duplex)
- 2.5 Gigabit: 5Gbps (full duplex)

Performance

- Switching Capacity: 25Gbps
- RAM Buffer: 1.5MB
- MAC Address Table: 16K entries
- Forwarding Rate: 18.6Mpps (64-byte packet size)
- Jumbo Frames: 12KB

Special Features

- Wall-Mountable

Power

- Input: 100 – 240V AC, 50/60 Hz, 0.5A
- Output: 12V DC, 1A external power adapter
- Max. Consumption: 9.5

Fan/Acoustics

- Fanless design

MTBF

- 674,176 hours

Operating Temperature

- 0° – 40° C (32° – 104° F)

Operating Humidity

- Max. 90% non-condensing

Dimensions (L x W x H)

- 160 x 25 x 109mm (6.29 x 0.98 x 4.29 in.)

Weight

- 414g (14.6 oz.)

Certifications

- FCC
- CE

Warranty

- 3 year

Package Contents

- TEG-S350
- Quick Installation Guide
- Power adapter (12V DC, 1.5A)

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

TRENDnet offers a lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.