



5-Port Industrial Gigabit PoE+ DIN-Rail Switch

TI-PG50 (v2.xR)

- 4 x Gigabit PoE+ ports
- 1 x Gigabit port
- Up to 120W PoE power budget
- Hardened IP50 rated metal switch
- Extreme operating temperature range of -40° – 75°C (-40° – 167°F)
- Dual inputs provide redundant power with overload current protection
- 10Gbps switching capacity
- Includes DIN-Rail mount and wall mount brackets
- Power supply sold separately (model: TI-S15052)
- Lifetime Warranty
- NDAA / TAA compliant (U.S. and Canada only)

TRENDnet's 5-Port Industrial Gigabit PoE+ DIN-Rail Switch, model TI-PG50, features a rugged IP50 rated metal enclosure. This industrial unmanaged PoE+ switch is designed to withstand a high degree of vibration and shock, while operating in both high and low temperatures for industrial environments within -40° – 75° C (-40° – 167° F). Redundant power inputs with overload current protection minimizes network downtime.

Installers and integrators can save on equipment costs and reduce installation time with TRENDnet's Industrial Gigabit PoE+ Switch by delivering up to 30W per port of PoE power and data over existing Ethernet cables. With PoE technology, users only need one cable to deliver both data and power from the industrial unmanaged PoE+ switch. Utilize TRENDnet's industrial PoE+ switch to easily network PoE devices, such as high-power wireless access points, PTZ and other advanced IP cameras, VoIP phone systems, IPTV decoders, access controls, and more.



PoE+ Power

Maximum A 120W PoE+ power budget supplies power up to four Power over Ethernet devices.



Fault Tolerance

The industrial unmanaged PoE+ switch features redundant power inputs for backup power.



Industrial Hardened Design

Rugged IP50 rated housing with a high degree of vibration and shock resistance, and an operating temperature range of -40° – 75° C (-40° – 167° F).

FEATURES



PoE+ Power

Up to 30W of power per port and data over a single Ethernet cable to PoE devices



Easy Installation

No configuration needed, simply connect PoE+ network devices to the industrial unmanaged PoE+ switch



DIN-Rail / Wall Mounts

The se rugged PoE+ switches each includes DIN-Rail mount and wall mount hardware included



IP50 Rated

This industrial media converter is IP50 rated for ingress dust protection



Redundant Power

Dual inputs provide redundant power with overload current protection (power supply sold separately, model: TI-S15052)



Extreme Temperature Range

An extreme operating temperature range of -40° – 75° C (-40° – 167° F) allows for installations in industrial environments with intense hot or cold conditions



Shock and Vibration Resistant

Rated for shock (EN 60068-2-27), freefall (EN 60068-2-32), and vibration (EN 60068-2-6)



Electro Magnetic Compliance



Complies with industrial EMS certifications ESD (IEC 61000-4-2); Contact: 6kV, Air: 8kV; EFT (IEC 61000-4-4): Power 2kV, Signal: 2kV; Surge (IEC 61000-4-5): Power: 2kV, Signal: 2kV



Grounding Point

The industrial unmanaged PoE+ switch features a grounding point to protect equipment from external electrical surges

NETWORKING SOLUTION



SPECIFICATIONS

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3x
- IEEE 802.3af
- IEEE 802.3at

Device Interface

- 4 x Gigabit PoE+ ports
- 1 x Gigabit port
- 4-pin removable terminal block
- LED indicators
- DIN-Rail mount
- Wall mount
- Grounding point

Data Transfer Rate

- Ethernet: 10Mbps (half duplex), 20Mbps (full duplex)
- Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex)
- Gigabit: 2Gbps (full duplex)

Performance

- Data RAM Buffer: 125KB
- Switching Fabric: 10Gbps
- MAC Address Table: 2K entries
- Jumbo Frame: 9KB
- Forwarding rate: 7.44Mpps (64-byte packet size)

DC Power

- Input: 48 - 56V DC
- Compatible power supply: TI-S15052 (sold separately)
- Max. consumption: 2.24W @ 48V DC (without PD)

PoE

- 802.3af PoE: up to 15.4W per port
- 802.3at PoE+: up to 30W per port
- Power budget: 60W - 120W
- PoE Mode A: Pins 1, 2, 3, and 6 for power

Terminal Block

- 4-pin terminal block
- Wire range: 0.34mm² to 2.5mm²
- Solid wire (AWG): 12-24
- Stranded wire (AWG): 12-24
- Torque: 5 lb. - In / 0.5Nm / 0.56 Nm
- Wire strip length: 7-8mm

MTBF

- 83,000 hours @ 25°C

Housing

- IP50 metal case
- DIN-Rail mount
- Wall mount
- Grounding point
- 6kV ESD protection

Operating Temperature

- - 40° - 75° C (-40 - 167° F)

Operating Humidity

- Max. 95% non-condensing

Dimensions

- 156 x 122 x 48mm (6.1 x 4.8 x 1.9 in.)

Weight

- 630g (1.38 lbs.)

Certifications

- CE
- FCC
- LVD
- Shock (IEC 60068-2-27)
- Freefall (IEC 60068-2-32)
- Vibration (IEC 60068-2-6)
- IEC 61000-4-2
- IEC 61000-4-4
- IEC 61000-4-5

Warranty

- Lifetime Warranty

Package Contents

- TI-PG50
- Removable terminal block
- DIN-Rail and wall mount kit

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

TRENDnet offers a lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.